


AGRIMAXFACTOR

| | |
|---------------------|--|
| TIRE SIZE | 580/70 R 42 |
| UM | US STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | TRACTOR |
| VERSION | STANDARD |
| TL/TT | TL |
| LI/SS | 158 D ; 161 A8 |



DIMENSIONS US STANDARD

| | | | |
|-----------------|----------|----------------|------------------|
| USA CODE | 94075836 | RC (IN) | 224.1 |
| SW (IN) | 22.7 | RIM REC | W 18 L |
| OD (IN) | 74.0 | RIM ALT | DW18L;DD18L |
| SLR (IN) | 33.7 | ECE | E11-106R-0010076 |

LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 9 | 12 | 15 | 17 | 20 | 23 |
|-----------|------|------|------|-------|-------|-------|
| 40 | 5160 | 6000 | 6840 | 7680 | 8530 | 9370 |
| 30 | 5420 | 6300 | 7190 | 8080 | 8960 | 9840 |
| 25 | 5610 | 6530 | 7450 | 8370 | 9280 | 10200 |
| 15 | 5930 | 6900 | 7870 | 8840 | 9810 | 10780 |
| 5 LT | 6910 | 8040 | 9170 | 10300 | 11430 | 12550 |
| 5 HT | 5930 | 6900 | 7870 | 8840 | 9810 | 10780 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.