


# AGRIMAX RT 765

<b>TIRE SIZE</b>	<b>650/75 R 42</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	PULVERIZATOR / TRACTOR / MAȘINĂ DE RECOLTAT PODGORII / MAȘINĂ DE RECOLTARE / MAȘINI DE IMPLEMENTARE
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	170 D



## DIMENSIUNI IS STANDARD

<b>SW (MM)</b>	655	<b>RIM REC</b>	DW21B
<b>OD (MM)</b>	2043	<b>RIM ALT</b>	DW20B;DW23B
<b>SLR (MM)</b>	916	<b>ECE</b>	E11-106R-006402
<b>RC (MM)</b>	6147	<b>SRI</b>	975

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4
<b>65</b>	2820	3240	3720	4200	4680	5160	5640	6000
<b>50</b>	2965	3405	3910	4410	4915	5420	5925	6300
<b>40</b>	3090	3550	4075	4600	5125	5655	6180	6570
<b>30</b>	3245	3730	4280	4830	5385	5935	6490	6900
<b>10 LT</b>	3780	4345	4985	5630	6275	6915	7560	8040
<b>10 HT</b>	3245	3730	4280	4830	5385	5935	6490	6900

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.