


EARTHMAX SR 31

| | |
|---------------------|------------------------------------------------------------------------------------------|
| TIRE SIZE | 23.5 R 25 |
| UM | US STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | LOADER / DOZER / ARTICULATED DUMP TRUCK / LOADER / DOZER |
| VERSION | CUT RESISTANT COMPOUND |
| TIRE TYPE | TL |
| LI/SS | 185 B ; 195 A2 |



DIMENSIONS US STANDARD

| | | | |
|-----------------|----------|--------------------|-----------|
| USA CODE | 94048434 | RIM REC | 19.50/2.5 |
| OD (IN) | 63.3 | TRA CODE | E3/L3 |
| SLR (IN) | 28.0 | STAR RATING | ★★★ |
| RC (IN) | 188.9 | | |

LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 58 | 62 | 65 | 69 | 73 | 76 |
|-----------|-------|-------|-------|-------|-------|-------|
| 30 | 16500 | 17100 | 18200 | 18700 | 19800 | 20400 |
| 5 | 22700 | 23400 | 24700 | 25400 | 26800 | -- |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.