


# AGRIMAX TERIS

<b>TIRE SIZE</b>	<b>1050/50 R 32 CHO</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	CEIFEIRA / COLHEDORA DE ALGODÃO
<b>VERSÃO</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	184 A8 ; 181 B



## DIMENSÕES US STANDARD

<b>CÓDIGO USA</b>	94032723	<b>RC (IN)</b>	223.8
<b>SW (IN)</b>	41.7	<b>RIM REC</b>	36.0 VA (multipiece)
<b>OD (IN)</b>	74.5	<b>ECE</b>	E4-106R-000813
<b>SLR (IN)</b>	33.1		

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	12	15	20	23	29	35	41	46
<b>30</b>	8190	9280	11640	12920	14370	15460	16920	18190
<b>25</b>	8930	10120	12700	14090	15670	16860	18450	19840
<b>20</b>	9560	10840	13590	15080	16780	18050	19750	21230
<b>10 CYC</b>	14740	16700	20950	23250	25870	27830	30460	32740
<b>5 CYC</b>	16070	18220	22860	25360	28220	30360	33220	35710

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.