

# LG 306

|                     |  |
|---------------------|--|
| <b>TIRE SIZE</b>    | <b>23X10.50 - 12</b>                                 |
| <b>UM</b>           | US STANDARD  |
| <b>CONSTRUCTION</b> | BIAS   |
| <b>MACHINERY</b>    | MAQUINA DE CORTAR RELVA / TRATOR<br>PEQUENO / TRATOR |
| <b>VERSÃO</b>       | STANDARD   |
| <b>TIRE TYPE</b>    | TL   |



## DIMENSÕES US STANDARD

|                   |          |                |                             |
|-------------------|----------|----------------|-----------------------------|
| <b>CÓDIGO USA</b> | 94012558 | <b>RC (IN)</b> | 66.8                        |
| <b>SW (IN)</b>    | 10.2     | <b>RIM REC</b> | 8.5   - 55                  |
| <b>OD (IN)</b>    | 23.0     | <b>RIM ALT</b> | 7.00   - 55;   - 70;   - 90 |
| <b>SLR (IN)</b>   | 10.3     | <b>ECE</b>     | E4-106R-002661              |

## LOAD CAPACITY (LBS/TIRE)

|                  |           |
|------------------|-----------|
| <b>MPH / PSI</b> | <b>44</b> |
| 10               | 2105      |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.