

AS 504

TIRE SIZE	7.00 - 12
UM	US STANDARD
CONSTRUCTION	⊠ BIAS
MACHINERY	ТЕЛЕСКОПИЧЕСКИЙ ПОГРУЗЧИК / ПРИЦЕП ДЛЯ ПОЛЕВЫХ РАБОТ / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ / ТЕЛЕСКОПИЧЕСКИЙ ПОГРУЗЧИК
VERSION	STANDARD
TIRE TYPE	TL
LI/SS DRIVE WHEEL	75 A8
LI/SS FREE ROLLING	88 A8



РАЗМЕРЫ US STANDARD

USA CODE	94019236	RC (IN)	80.7
SW (IN)	7.4	RIM REC	4.5
OD (IN)	26.9	ECE	E4-106R-002207
SLR (IN)	12.2	PR	4

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	25
5 FR	1730
15 FR	1470
20 FR	1380
25 FR	1230
5 DW	1190
15 DW	1010
20 DW	950
25 DW	850

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.