DATA SHEET

PRINTED ON
21-04-2026

AS 504

TIRE SIZE	**7.50 - 16**
UM	US STANDARD
CONSTRUCTION	BIAS
MACHINERY	MAQUINARIA AGRÍCOLA / ELEVADOR TELESCÓPICO / REMOLQUE / EWMOLQUE PARA CAMPOS / MAQUINARIA AGRÍCOLA / ELEVADOR TELESCÓPICO
VERSIÓN	STANDARD
TIRE TYPE	TT
LI/SS DRIVE WHEEL	99 A8
LI/SS FREE ROLLING	112 A8

DIMENSIONES US STANDARD

CÓDIGO USA	94019328	**RC (IN)**	97.4
SW (IN)	8.2	**RIM REC**	5.50 F
OD (IN)	31.6	**RIM ALT**	4.50 E; 5.00 F; 4.00 E; 5 K; 6 LB; 6.00 F
SLR (IN)	14.6	**ECE**	E4-106R-002633

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	46
5 FR	3460
15 FR	2940
20 FR	2770
25 FR	2470
5 DW	2390
15 DW	2030
20 DW	1920
25 DW	1710

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..