


FL 695

TIRE SIZE	710/50 R 30.5
UM	US STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	RIMORCHIO / ATTREZZI AGRICOLI / RIMORCHIO
VERSIONE	STEEL BELTED
TIRE TYPE	TL
LI/SS	177 D



DIMENSIONI US STANDARD

CODICE USA	94074082	RC (IN)	179.3
SW (IN)	27.6	RIM REC	AG24.00
OD (IN)	58.7	RIM ALT	AG20.00
SLR (IN)	27.2	ECE	E11-106R-008661

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	12	17	23	29	35	41	46	52	58	65	73
40	--	--	--	8210	9500	10790	11920	13040	14330	15290	16090
30	--	--	--	9940	11500	13050	14420	15780	17340	18510	19480
25	--	8100	9850	11170	12920	14670	16200	17740	19490	20800	21890
20	7050	8990	10950	12400	14340	16290	17990	19700	21640	23090	24300
15	7390	9410	11450	12970	15010	17040	18830	20600	22640	24160	25430
10	7700	9830	11960	13550	15670	17800	19650	21520	23640	25230	26550
5	8410	10720	13040	14780	17100	19410	21440	23470	25780	27520	28970

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.