


# AGRIMAX PROHARVEST

VF 900/60 R 32

UM IS STANDARD

CONSTRUCTION  RADIAL

MACHINERY BIÇERDÖVER

VERSION STEEL BELTED

TIRE TYPE TL

193 D



## UNDEFINED IS STANDARD

|          |      |         |                  |
|----------|------|---------|------------------|
| SW (MM)  | 881  | RIM REC | DW 30 B          |
| OD (MM)  | 1900 | ECE     | E11-106R-0010580 |
| SLR (MM) | 837  | SRI     | 900              |
| RC (MM)  | 5712 |         |                  |

## LOAD CAPACITY (KG/TIRE)

| KM/H / BAR    | 0.6  | 0.8  | 1.0  | 1.2  | 1.4   | 1.6   | 2.0   | 2.4   | 2.8   | 3.2   |
|---------------|------|------|------|------|-------|-------|-------|-------|-------|-------|
| 70            | 4085 | 4710 | 5340 | 6070 | 6700  | 7435  | 8270  | 8375  | 9735  | 10465 |
| FROM 65 TO 40 | 4485 | 5175 | 5865 | 6670 | 7360  | 8165  | 9085  | 9200  | 10695 | 11500 |
| 30            | 4575 | 5280 | 5985 | 6805 | 7510  | 8330  | 9270  | 9385  | 10910 | 11730 |
| 20            | 4665 | 5385 | 6100 | 6940 | 7655  | 8495  | 9450  | 9570  | 11125 | 11960 |
| 10            | 4935 | 5695 | 6455 | 7340 | 8100  | 8985  | 9995  | 10120 | 11765 | 12650 |
| UPTO 30 CYC   | 5095 | 5875 | 6660 | 7575 | 8360  | 9270  | 10315 | 10445 | 12145 | 13055 |
| UPTO 15 CYC   | 6080 | 7015 | 7950 | 9040 | 9975  | 11070 | 12315 | 12470 | 14495 | 15585 |
| UPTO 10 CYC   | 6665 | 7690 | 8715 | 9910 | 10935 | 12130 | 13495 | 13665 | 15885 | 17080 |
| 10HT          | 4575 | 5280 | 5985 | 6805 | 7510  | 8330  | 9270  | 9385  | 10910 | 11730 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.