

AGRIMAX TURF RT 333

| | |
|---------------------|---|
| TIRE SIZE | 240/60 R 12 |
| UM | IS STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | КОМБАЙН ДЛҮА УБОРКИ ВИНОГРАДА / МАШИНА ДЛҮА СБОРА ФРУКТОВ / МИНИ- ТРАКТОР / ТРАКТОР-ТЯГАЧ / КОМБАЙН |
| VERSION | STANDARD |
| TIRE TYPE | TL |
| LI/SS | 89 A8 ; B |



РАЗМЕРЫ IS STANDARD

| | | | |
|-----------------|------|----------------|-----------------|
| SW (MM) | 242 | RIM REC | 7 |
| OD (MM) | 592 | ECE | E11-106R-007679 |
| SLR (MM) | 269 | | |
| RC (MM) | 1777 | | |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 0.6 | 0.8 | 1.0 | 1.2 | 1.4 | 1.6 | 2.0 | 2.4 |
|------------|-----|-----|-----|-----|-----|-----|-----|-----|
| 50 | 270 | 310 | 355 | 395 | 445 | 485 | 540 | 580 |
| 40 | 270 | 310 | 355 | 395 | 445 | 485 | 540 | 580 |
| 30 | 290 | 335 | 385 | 425 | 475 | 520 | 585 | 625 |
| 10 LT | 360 | 415 | 480 | 535 | 595 | 650 | 730 | 780 |
| 10 HT | 290 | 335 | 385 | 425 | 475 | 520 | 585 | 625 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.