


RIDEMAX FL 693 M

| | |
|---------------------|--|
| TIRE SIZE | 500/60 R 22.5 |
| UM | IS STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | CISTERNĂ / REMORCĂ / MAȘINI DE IMPLEMENTARE |
| VERSION | STANDARD |
| TIRE TYPE | TL |
| LI/SS | 163 D |



DIMENSIUNI IS STANDARD

| | | | |
|-----------------|------|----------------|-----------------|
| SW (MM) | 503 | RIM REC | AG 16.00 |
| OD (MM) | 1172 | RIM ALT | 15.00; 17.00 |
| SLR (MM) | 544 | ECE | E11-106R-007203 |
| RC (MM) | 3625 | SRI | 550 |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 1.2 | 1.6 | 2 | 2.4 | 2.8 | 3.2 | 3.6 | 4 | 4.5 | 5 | 5.5 | 6.0 |
|------------|------|------|------|------|------|------|------|------|------|------|------|------|
| 70 | 1470 | 1825 | 2000 | 2310 | 2620 | 2890 | 3155 | 3465 | 3690 | 3910 | 4175 | 4440 |
| 65 | 1610 | 2000 | 2195 | 2535 | 2880 | 3170 | 3465 | 3805 | 4050 | 4290 | 4585 | 4875 |
| 50 | 1950 | 2420 | 2655 | 3070 | 3485 | 3835 | 4190 | 4605 | 4900 | 5195 | 5550 | 5900 |
| 40 | 2190 | 2720 | 2985 | 3450 | 3915 | 4310 | 4710 | 5175 | 5505 | 5835 | 6235 | 6630 |
| 25 | 2545 | 3160 | 3470 | 4010 | 4550 | 5010 | 5475 | 6010 | 6400 | 6785 | 7245 | 7705 |
| 10 | 2900 | 3600 | 3950 | 4565 | 5180 | 5705 | 6235 | 6845 | 7285 | 7725 | 8250 | 8775 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.