


# AGRIMAX RT 765

|                     |  |
|---------------------|--|
| <b>TYRE SIZE</b>    | <b>480/70 R 34</b>   |
| <b>UM</b>           | US STANDARD  |
| <b>CONSTRUCTION</b> |  RADIAL |
| <b>MACHINERY</b>    | TRACTOR / IMPLEMENTS   |
| <b>VERSION</b>      | SPECIAL  |
| <b>TYRE TYPE</b>    | TL   |
| <b>LI/SS</b>        | 155 D  |



## DIMENSIONS US STANDARD

|                 |          |                |                 |
|-----------------|----------|----------------|-----------------|
| <b>USA CODE</b> | 94063284 | <b>RC (IN)</b> | 188.5           |
| <b>SW (IN)</b>  | 18.9     | <b>RIM REC</b> | W 15 L          |
| <b>OD (IN)</b>  | 62.2     | <b>RIM ALT</b> | W 14 L; W 16 L  |
| <b>SLR (IN)</b> | 28.7     | <b>ECE</b>     | E11-106R-005834 |

## LOAD CAPACITY (LBS/TYRE)

| MPH / PSI | 9    | 12   | 15   | 17   | 20   | 23   | 29   | 35   | 41    | 47    |
|-----------|------|------|------|------|------|------|------|------|-------|-------|
| 40        | 3340 | 3940 | 4530 | 5050 | 5640 | 6150 | 6760 | 7260 | 7950  | 8540  |
| 30        | 3510 | 4130 | 4760 | 5300 | 5930 | 6470 | 7100 | 7630 | 8360  | 8970  |
| 25        | 3660 | 4310 | 4960 | 5520 | 6180 | 6750 | 7400 | 7960 | 8710  | 9360  |
| 20        | 3840 | 4530 | 5210 | 5810 | 6490 | 7090 | 7770 | 8370 | 9150  | 9830  |
| 5 LT      | 4480 | 5270 | 6070 | 6770 | 7560 | 8260 | 9050 | 9740 | 10660 | 11450 |
| 5 HT      | 3840 | 4530 | 5210 | 5810 | 6490 | 7090 | 7770 | 8370 | 9150  | 9830  |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.