


AGRIMAX SPARGO

TIRE SIZE	VF 380/105 R 50
UM	IS STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	TRATOR
VERSÃO	STANDARD
TIRE TYPE	TL
LI/SS	179 D



DIMENSÕES IS STANDARD

SW (MM)	400	RIM REC	W 13 A
OD (MM)	2050	RIM ALT	W 12; DW 12; DW 13; DW 13 L
SLR (MM)	934	ECE	E4-106R-002397
RC (MM)	6211	SRI	975

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	1.2	1.4	1.6	1.8	2.0	2.2	2.4	2.6	2.8	3.0	3.2	3.4	3.6	3.8	4.0	4.2	4.4
70	3380	3805	4155	4370	4580	4720	4860	5145	5355	5565	5780	5990	6130	6345	6485	6765	7050
FROM 65 TO 40	3720	4185	4570	4805	5035	5190	5345	5655	5890	6120	6355	6585	6740	6975	7130	7440	7550
30	3790	4265	4660	4990	5135	5295	5450	5770	6005	6240	6480	6715	6875	7110	7270	7585	7905
20	3865	4350	4755	4995	5235	5400	5560	5880	6125	6365	6605	6850	7010	7250	7415	7735	8060
10	4090	4600	5025	5285	5540	5710	5880	6220	6475	6730	6990	7245	7415	7670	7840	8180	8525

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.