


# EARTHMAX SR 47 TP

|                     |  |
|---------------------|--|
| <b>TIRE SIZE</b>    | <b>24.00 R 35</b>  |
| <b>UM</b>           | US STANDARD  |
| <b>CONSTRUCTION</b> |  RADIAL |
| <b>MACHINERY</b>    | САМОСВАЛ С ЖЕСТКОЙ РАМОЙ   |
| <b>VERSION</b>      | STANDARD COMPOUND  |
| <b>TIRE TYPE</b>    | TL   |
| <b>LI/SS</b>        | 209 B  |



## РАЗМЕРЫ US STANDARD

|                 |          |                    |           |
|-----------------|----------|--------------------|-----------|
| <b>USA CODE</b> | 94074211 | <b>RIM REC</b>     | 17.00/3.5 |
| <b>OD (IN)</b>  | 86.0     | <b>TRA CODE</b>    | E4        |
| <b>SLR (IN)</b> | 38.8     | <b>STAR RATING</b> | ★★        |
| <b>RC (IN)</b>  | 260.8    |                    |           |

## LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 73    | 76    | 80    | 83    | 87    | 91    | 94    | 98    | 102   |
|-----------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
| 30        | 30900 | 32000 | 34200 | 35300 | 36400 | 37500 | 38600 | 39700 | 40800 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.