

AGRIMAX RT 657

TIRE SIZE	650/65 R 38
UM	IS STANDARD
MACHINERY	TRAUBENERNTEMASCHINE / TRACTOR / ERNTEMASCHINE
VERSION	STANDARD
TIRE TYPE	TL
LI/SS	163 D ; 166 A8

ABMESSUNGEN IS STANDARD

SW (MM)	645	RIM REC	DW 20 B
OD (MM)	1811	RIM ALT	DW 21 B ; DW 23 B
SLR (MM)	830	ECE	E4-106R-000624
RC (MM)	5483	SRI	875

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4
65	2340	2730	3075	3415	3755	4050	4485	4875
50	2460	2870	3230	3585	3945	4250	4715	5120
40	2545	2970	3340	3710	4085	4400	4880	5300
30	2695	3145	3535	3930	4320	4660	5165	5610
10 LT	3140	3660	4120	4575	5035	5425	6015	6535
10 HT	2695	3145	3535	3930	4320	4660	5165	5610

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

