


# AGRIMAX FORCE

<b>TIRE SIZE</b>	<b>IF 710/60 R 30</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	MAȘINĂ DE RECOLTARE / TRACTOR DE MARE PUTERE / TRACTOR
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	168 D



## DIMENSIUNI US STANDARD

<b>USA CODE</b>	94038541	<b>RC (IN)</b>	189.5
<b>SW (IN)</b>	27.9	<b>RIM REC</b>	DW 25 B
<b>OD (IN)</b>	63.5	<b>ECE</b>	E4-106R-001407
<b>SLR (IN)</b>	28.1	<b>TRA CODE</b>	R1W

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23	29	35
45	5160	5940	6840	7630	8530	9310	10440	11230
<b>FROM 40 TO 25</b>	5680	6540	7530	8390	9380	10240	11470	12300
20	5900	6790	7830	8720	9750	10650	11930	12830
12	6130	7050	8120	9050	10130	11060	12390	13330
5	7210	8300	9560	10650	11900	13000	14570	15670
<b>UPTO 20 CYC</b>	7370	8490	9780	10900	12190	13300	14910	16050
<b>UPTO 10 CYC</b>	8800	10130	11660	13000	14540	15860	17780	19140
<b>UPTO 5 CYC</b>	9640	11110	12800	14250	15940	17400	19500	20990
5 HT	5900	6790	7830	8720	9750	10650	11930	12830

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.