


AGRIMAX RT 600

| | |
|---------------------|--|
| TYRE SIZE | 800/65 R 32 |
| UM | IS STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | TRACTOR / IMPLEMENTS |
| VERSION | STANDARD |
| TYRE TYPE | TL |
| LI/SS | 176 A8 ; 173 B |



DIMENSIONS IS STANDARD

| | | | |
|-----------------|------|----------------|------------------|
| SW (MM) | 775 | RIM REC | DW 27 B |
| OD (MM) | 1820 | RIM ALT | DH 27 B; DW 25 B |
| SLR (MM) | 823 | ECE | E4-106R-001428 |
| RC (MM) | 5558 | SRI | 875 |

LOAD CAPACITY (KG/TYRE)

| KM/H / BAR | 0.8 | 1.0 | 1.2 | 1.6 | 2.0 | 2.4 | 2.8 | 3.0 | 3.2 | 3.6 |
|------------|------|------|------|------|------|-------|-------|-------|-------|-------|
| 50 | 3175 | 3660 | 4485 | 4900 | 5385 | 5865 | 6350 | 6500 | - | - |
| 40 | 3450 | 3975 | 4875 | 5325 | 5850 | 6375 | 6900 | 7100 | - | - |
| 30 | 3695 | 4255 | 5220 | 5700 | 6260 | 6825 | 7385 | 7600 | - | - |
| 10 LT | 4625 | 5330 | 6535 | 7140 | 7840 | 8545 | 9250 | 9515 | - | - |
| 10 HT | 3695 | 4255 | 5220 | 5700 | 6260 | 6825 | 7385 | 7600 | - | - |
| 10 CYC. | - | 5655 | 7230 | 7960 | 9250 | 10140 | 11055 | 11540 | 12025 | 12440 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.