


# AGRIMAX V- FLECTO

TIRE SIZE	VF 710/60 R 38
UM	US STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	TRATOR DE ALTA POTENCIA / TRATOR
VERSÃO	STANDARD
TIRE TYPE	TL
LI/SS	171 D



## DIMENSÕES US STANDARD

CÓDIGO USA	94058563	RC (IN)	214.4
SW (IN)	27.9	RIM REC	DW 25 B
OD (IN)	71.7	RIM ALT	DW 23 B
SLR (IN)	31.3	ECE	E11-106R-004520

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23
45	6780	7890	8990	10110	11220	12330
FROM 40 TO 25	7450	8670	9890	11110	12330	13560
20	7590	8840	10070	11330	12580	13820
12	7750	9020	10270	11550	12820	14100
5	8190	9530	10870	12210	13560	14910
*UPTO 5 CYC WITH FRONT LOADER	10430	12140	13830	15550	17260	18980
5 HT	7590	8840	10070	11330	12580	13820

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.