


# AGRIMAX RT 955

|                     |  |
|---------------------|--|
| <b>TIRE SIZE</b>    | 270/95 R 32  |
| <b>UM</b>           | IS STANDARD  |
| <b>CONSTRUCTION</b> |  RADIAL |
| <b>MACHINERY</b>    | BESPRUTNINGSBIL / SKÖRDEMASKIN<br>FÖR VINGÅRD / SKÖRDEMASKIN /<br>ARBETSFORDON           |
| <b>VERSION</b>      | STANDARD   |
| <b>TIRE TYPE</b>    | TL   |
| <b>LI/SS</b>        | 136 A8/B   |



## DIMENSIONER IS STANDARD

|                 |      |                |                |
|-----------------|------|----------------|----------------|
| <b>SW (MM)</b>  | 275  | <b>RIM REC</b> | W 9            |
| <b>OD (MM)</b>  | 1327 | <b>RIM ALT</b> | W 8; W 10      |
| <b>SLR (MM)</b> | 614  | <b>ECE</b>     | E4-106R-000776 |
| <b>RC (MM)</b>  | 4076 | <b>SRI</b>     | 625            |

## LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 0.8  | 1.2  | 1.6  | 2.0  | 2.4  | 2.8  | 3.2  | 3.6  | 4.0  | 4.4  |
|------------|------|------|------|------|------|------|------|------|------|------|
| 50         | 875  | 1145 | 1390 | 1525 | 1615 | 1770 | 1930 | 2085 | 2240 | -    |
| 40         | 875  | 1145 | 1390 | 1525 | 1615 | 1770 | 1930 | 2085 | 2240 | -    |
| 30         | 940  | 1225 | 1490 | 1635 | 1730 | 1900 | 2065 | 2235 | 2400 | -    |
| 10         | 1045 | 1315 | 1615 | 1920 | 2220 | 2285 | 2555 | 2825 | 3095 | 3360 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.