


# AGRIMAX SPARGO

<b>TIRE SIZE</b>	<b>VF 480/80 R 46</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	TRACTOR
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	177 D



## DIMENSIONS IS STANDARD

<b>SW (MM)</b>	479	<b>RIM REC</b>	DW 16 L
<b>OD (MM)</b>	1936	<b>RIM ALT</b>	DW 15 L
<b>SLR (MM)</b>	892	<b>ECE</b>	E11-106R-004756-01
<b>RC (MM)</b>	5907	<b>SRI</b>	925

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	1.2	1.4	1.6	1.8	2.0	2.2	2.4	2.6	2.8	3.0	3.2	3.4	3.6
<b>70</b>	3715	4115	4515	4710	4980	5110	5245	5510	5775	5975	6240	6440	6640
<b>FROM 65 TO 40</b>	4085	4525	4960	5180	5475	5620	5765	6055	6350	6570	6860	7080	7300
<b>30</b>	4165	4615	5060	5285	5580	5730	5880	6175	6475	6700	6995	7220	7445
<b>20</b>	4250	4705	5160	5385	5690	5840	5995	6295	6600	6830	7130	7360	7590
<b>10</b>	4495	4975	5460	5700	6020	6180	6340	6660	6985	7225	7545	7785	8030

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.