

# XL GRIP (E3)

|                     |                                                                                        |
|---------------------|----------------------------------------------------------------------------------------|
| <b>TIRE SIZE</b>    | <b>18.00 - 33</b>                                                                      |
| <b>UM</b>           | IS STANDARD                                                                            |
| <b>CONSTRUCTION</b> |  BIAS |
| <b>MACHINERY</b>    | STEL DUMPER                                                                            |
| <b>VERSION</b>      | STANDARD                                                                               |
| <b>TIRE TYPE</b>    | TL                                                                                     |



## DIMENSIONER IS STANDARD

|                 |           |                 |    |
|-----------------|-----------|-----------------|----|
| <b>OD (MM)</b>  | 1820      | <b>PR</b>       | 32 |
| <b>SLR (MM)</b> | 840       | <b>TRA CODE</b> | E3 |
| <b>RC (MM)</b>  | 5385      |                 |    |
| <b>RIM REC</b>  | 13.00/2.5 |                 |    |

## LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 5.75  | 7.50  |
|------------|-------|-------|
| 50         | 10300 | -     |
| 10         | -     | 17500 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.