


MULTIMAX MP 522

TIRE SIZE	440/80 R 28 IND
UM	US STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	CARREGADORA COMPACTA / LEVANTADOR TELESCÓPICO / CARREGADORA COMPACTA / LEVANTADOR TELESCÓPICO
VERSÃO	STANDARD
TIRE TYPE	TL
LI/SS	156 A8/B



DIMENSÕES US STANDARD

CÓDIGO USA	94052240	RC (IN)	168.4
SW (IN)	17.4	RIM REC	DW 14 L
OD (IN)	55.7	RIM ALT	DW 13 ; DW 13 L ; DW 15 L
SLR (IN)	25.3	ECE	E11-106R-002968

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	23	29	32	35	38	41	44	46	49	52
30	5070	6010	6480	6940	7410	7880	8360	8820	-	-
25	5070	6010	6480	6940	7410	7880	8360	8820	-	-
20	5470	6460	6960	7450	7950	8440	8940	9440	-	-
15	5670	6700	7210	7730	8240	8750	9270	9790	-	-
5 CYC.	6260	7650	8360	9050	9740	10440	11130	11840	12530	13230
STATIC	9610	11750	12810	13880	14950	16020	17080	18140	19210	20280

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.