

AGRIMAX RT 855

TIRE SIZE	520/85 R 38
UM	US STANDARD
MACHINERY	PULVERIZADOR / VENDIMIADORA / TRACTOR / COSECHADORA / MAQUINARIA AGRÍCOLA
VERSIÓN	STANDARD
TIRE TYPE	TL
LI/SS	170 A8/B

DIMENSIONES US STANDARD

CÓDIGO USA	94038374	RC (IN)	220.3
SW (IN)	20.3	RIM REC	DW 16 L
OD (IN)	72.8	RIM ALT	DW 18 L ; DD 16 L
SLR (IN)	33.3	ECE	E4-106R-001411

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	17	23	29	35	41	46	52
30	4780	5640	7180	8540	9790	10450	11510	12430	13230
25	4780	5640	7180	8540	9790	10450	11510	12430	13230
20	5130	6040	7690	9150	10480	11190	12320	13300	14150
5 LT	6420	7560	9620	11450	13120	14010	15420	16670	17720
5 HT	5130	6040	7690	9150	10480	11190	12320	13300	14150

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

