

# FLOTATION 648

<b>TIRE SIZE</b>	<b>750/60 - 30.5</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	⊗ BIAS
<b>MACHINERY</b>	EMPACADORA DE HENO / COSECHADORA / ESPARCIDOR / COSECHADORA / MAQUINARIA AGRÍCOLA
<b>VERSIÓN</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS DRIVE WHEEL</b>	170 A8/167 B
<b>LI/SS FREE ROLLING</b>	182 A8/179 B



## DIMENSIONES IS STANDARD

<b>SW (MM)</b>	754	<b>RIM REC</b>	AG 24.00
<b>OD (MM)</b>	1675	<b>ECE</b>	E4-106R-001552
<b>SLR (MM)</b>	710	<b>PR</b>	16
<b>RC (MM)</b>	4935		

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	1.80	2.00	2.20
10 FR	10585	11255	11900
20 FR	9525	10130	10710
30 FR	8465	9005	9520
40 FR	7560	8040	8500
50 FR	6805	7235	7750
10 DW	7470	7945	8400
20 DW	6720	7150	7560
30 DW	5975	6355	6720
40 DW	5335	5675	6000
50 DW	4800	5110	5450

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.