


AGRIMAX V- FLECTO

TIRE SIZE	VF 710/60 R 42
UM	US STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	HOCHLEISTUNGSTRAKTOR / TRACTOR
VERSION	STANDARD
TIRE TYPE	TL
LI/SS	173 D



ABMESSUNGEN US STANDARD

USA-CODE	94053377	RC (IN)	227.8
SW (IN)	28.0	RIM REC	DW 25 B
OD (IN)	76.0	RIM ALT	DW 23 B; MW 25 B
SLR (IN)	33.9	ECE	E11-106R-002998

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23
45	7160	8340	9510	10690	11860	13040
FROM 40 TO 25	7880	9170	10460	11750	13040	14330
20	8040	9350	10660	11980	13290	14620
12	8190	9530	10870	12210	13560	14900
5	8660	10090	11500	12920	14340	15760
*UPTO 5 CYC WITH FRONT LOADER	11030	12830	14640	16450	18250	20060
5 HT	8040	9350	10660	11980	13290	14620

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.