


# EARTHMAX SR 315 CS

|                     |  |
|---------------------|--|
| <b>TIRE SIZE</b>    | <b>35/65 R 33</b>  |
| <b>UM</b>           | IS STANDARD  |
| <b>CONSTRUCTION</b> |  RADIAL |
| <b>MACHINERY</b>    | CARGADORA LHD / PALA CARGADORA   |
| <b>VERSIÓN</b>      | CUT RESISTANT COMPOUND   |
| <b>TIRE TYPE</b>    | TL   |
| <b>LI/SS</b>        | 229 A2   |



## DIMENSIONES IS STANDARD

|                 |           |                    |     |
|-----------------|-----------|--------------------|-----|
| <b>OD (MM)</b>  | 1948      | <b>TRA CODE</b>    | L3S |
| <b>SLR (MM)</b> | 867       | <b>STAR RATING</b> | ★★★ |
| <b>RC (MM)</b>  | 5886      |                    |     |
| <b>RIM REC</b>  | 28.00/3.5 |                    |     |

## LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 6.75  | 7.00  | 7.25  | 7.50  | 7.75  | 8.00  |
|------------|-------|-------|-------|-------|-------|-------|
| 10         | 29000 | 30000 | 30750 | 31500 | 32000 | 32500 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.