


# BK-LOADER 53

|                     |                                                                                          |
|---------------------|------------------------------------------------------------------------------------------|
| <b>TIRE SIZE</b>    | <b>405/70 R 18</b>                                                                       |
| <b>UM</b>           | US STANDARD                                                                              |
| <b>CONSTRUCTION</b> |  RADIAL |
| <b>MACHINERY</b>    | ПОГРУЗЧИК                                                                                |
| <b>VERSION</b>      | ARAMID BELTED                                                                            |
| <b>TIRE TYPE</b>    | TL                                                                                       |
| <b>LI/SS</b>        | 153A2/149A4                                                                              |



## РАЗМЕРЫ US STANDARD

|                 |          |                |                       |
|-----------------|----------|----------------|-----------------------|
| <b>USA CODE</b> | 94069705 | <b>RIM ALT</b> | 14; 13 SDC; 12;12 SDC |
| <b>SW (IN)</b>  | 16.0     |                |                       |
| <b>OD (IN)</b>  | 41.1     |                |                       |
| <b>RIM REC</b>  | 13       |                |                       |

## LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 22   | 29   | 36   | 44   | 51   | 58   | 65    | 73    | 80    |
|-----------|------|------|------|------|------|------|-------|-------|-------|
| 12        | 2520 | 3230 | 3810 | 4380 | 5020 | 5530 | 6100  | 6600  | 7170  |
| 5         | 2830 | 3630 | 4270 | 4920 | 5640 | 6210 | 6850  | 7410  | 8050  |
| STATIC    | 4520 | 5810 | 6850 | 7880 | 9030 | 9940 | 10970 | 11880 | 12900 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.