

FLOTATION 648

| | |
|---------------------------|---|
| TIRE SIZE | 800/45 - 26.5 |
| UM | IS STANDARD |
| CONSTRUCTION | ⊠ BIAS |
| MACHINERY | PRESSE À PAILLE / MOISSONNEUSE / ÉPANDEUR / MOISSONNEUSE / OUTILLAGE AGRICOLE |
| VERSION | STANDARD |
| TIRE TYPE | TL |
| LI/SS DRIVE WHEEL | 158 A8/155 B |
| LI/SS FREE ROLLING | 170 A8/167 B |



DIMENSIONS IS STANDARD

| | | | |
|-----------------|------|----------------|-----------------|
| SW (MM) | 800 | RIM REC | AG 28.00 |
| OD (MM) | 1393 | ECE | E11-106R-004557 |
| SLR (MM) | 631 | PR | 12 |
| RC (MM) | 4185 | | |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 1.50 | 1.60 | 1.70 |
|------------|------|------|------|
| 10 FR | 7805 | 8105 | 8400 |
| 20 FR | 7025 | 7295 | 7560 |
| 30 FR | 6245 | 6485 | 6720 |
| 40 FR | 5575 | 5790 | 6000 |
| 50 FR | 5020 | 5210 | 5450 |
| 10 DW | 5530 | 5740 | 5950 |
| 20 DW | 4975 | 5165 | 5355 |
| 30 DW | 4425 | 4590 | 4760 |
| 40 DW | 3950 | 4100 | 4250 |
| 50 DW | 3555 | 3690 | 3875 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.