


RIDEMAX FL 693 M



TIRE SIZE	710/50 R 26.5
UM	US STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	TANKBIL / SLÄPVAGN / ARBETSFORDON
VERSION	HD
TIRE TYPE	TL
LI/SS	179 D

DIMENSIONER US STANDARD

USA CODE	94063673	RC (IN)	166.0
SW (IN)	28.6	RIM REC	AG 24.00
OD (IN)	54.4	RIM ALT	AG 20.00
SLR (IN)	23.9	ECE	E11-106R-006008

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	15	17	23	29	35	41	46	52	58	73	87
45	3890	4980	6230	7000	8090	9180	10120	11040	12140	13690	15550
40	4280	5470	6830	7690	8880	10090	11110	12140	13330	15030	17080
30	5170	6620	8280	9310	10760	12200	13450	14680	16140	18200	20680
25	5810	7440	9300	10460	12090	13710	15110	16500	18130	20460	23240
20	6460	8270	10330	11620	13430	15230	16780	18330	20130	22720	25800
15	6760	8640	10800	12160	14040	15930	17550	19170	21060	23760	26990
5	7690	9840	12300	13840	15990	18150	19990	21840	24000	27070	30750

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.