

# TF 8181

|                     |  |
|---------------------|--|
| <b>TIRE SIZE</b>    | <b>6.50 - 20</b>                       |
| <b>UM</b>           | IS STANDARD                            |
| <b>CONSTRUCTION</b> | ❖ BIAS                                 |
| <b>MACHINERY</b>    | TRATTORE 2WD / TRATTORE /<br>RIMORCHIO |
| <b>VERSIONE</b>     | STANDARD                               |
| <b>TIRE TYPE</b>    | TT                                     |
| <b>LI/SS</b>        | 97 A6                                  |



## DIMENSIONI IS STANDARD

|                 |      |                |                |
|-----------------|------|----------------|----------------|
| <b>SW (MM)</b>  | 180  | <b>RIM REC</b> | 5.00 F         |
| <b>OD (MM)</b>  | 865  | <b>RIM ALT</b> | 4.00 E; 5.50 F |
| <b>SLR (MM)</b> | 409  | <b>ECE</b>     | E4-106R-001964 |
| <b>RC (MM)</b>  | 2578 | <b>PR</b>      | 6              |

## LOAD CAPACITY (KG/TIRE)

|                   |             |
|-------------------|-------------|
| <b>KM/H / BAR</b> | <b>3.10</b> |
| 30                | 730         |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.