

# EM 937 E3 (L)

|                     |                               |
|---------------------|-------------------------------|
| <b>TIRE SIZE</b>    | <b>14.00 - 24</b>             |
| <b>UM</b>           | IS STANDARD                   |
| <b>CONSTRUCTION</b> | ❖ BIAS                        |
| <b>MACHINERY</b>    | RETROESCAVADORA / CARREGADORA |
| <b>VERSÃO</b>       | STANDARD                      |
| <b>TIRE TYPE</b>    | TL                            |



## DIMENSÕES IS STANDARD

|                 |         |                 |       |
|-----------------|---------|-----------------|-------|
| <b>OD (MM)</b>  | 1368    | <b>PR</b>       | 20    |
| <b>SLR (MM)</b> | 628     | <b>TRA CODE</b> | E3/L3 |
| <b>RC (MM)</b>  | 4050    |                 |       |
| <b>RIM REC</b>  | 10.00 W |                 |       |

## LOAD CAPACITY (KG/TIRE)

| <b>KM/H / BAR</b> | <b>4.75</b> | <b>7.00</b> |
|-------------------|-------------|-------------|
| 50                | 4625        | -           |
| 10                | -           | 8500        |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.