


AGRIMAX SPARGO

TIRE SIZE	VF 380/90 R 50
UM	US STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	ТРАКТОР-ТЯГАЧ
VERSION	STANDARD
TIRE TYPE	TL
LI/SS	175 D



РАЗМЕРЫ US STANDARD

USA CODE	94065264	RC (IN)	234.3
SW (IN)	15.4	RIM REC	W13 B
OD (IN)	76.8	RIM ALT	W12 B
SLR (IN)	35.2	ECE	E11-106R-006400

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	17	20	23	26	29	32	35	38	41	44	47	49	52	55	58	51	64
45	6640	7470	8160	8580	8990	9260	9540	10100	10510	10930	11350	11750	12030	12450	12720	13280	13840
FROM 40 TO 25	7300	8220	8980	9430	9890	10190	10500	11100	11560	12020	12470	12930	13230	13690	13990	14600	15220
20	7450	8370	9150	9620	10080	10390	10700	11330	11790	12250	12710	13180	13500	13960	14270	14890	15510
12	7590	8540	9330	9800	10280	10600	10920	11550	12020	12490	12970	13440	13760	14240	14550	15180	15820
5	8030	9030	9870	10380	10870	11210	11550	12220	12710	13220	13720	14220	14550	15060	15390	16060	16740

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.