

# AGRIMAX RT 855

<b>TIRE SIZE</b>	<b>420/85 R 34</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	
<b>MACHINERY</b>	SPRAYER / VINEYARD HARVESTER / TRACTOR / HARVESTER / IMPLEMENTS
<b>VERSION</b>	STANDARD
<b>TL/TT</b>	TL
<b>LI/SS</b>	147 A8/B



## DIMENSIONS US STANDARD

<b>USA CODE</b>	94058532	<b>RC (IN)</b>	188.3
<b>SW (IN)</b>	17.2	<b>RIM REC</b>	W 15 L
<b>OD (IN)</b>	62.1	<b>RIM ALT</b>	W 13 ; W 14 L
<b>SLR (IN)</b>	28.7	<b>ECE</b>	E11-106R-005179

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23	29	35
30	3200	3670	4210	4750	5290	5830	6380	6780
25	3200	3670	4210	4750	5290	5830	6380	6780
20	3420	3920	4510	5090	5680	6250	6830	7260
5 LT	4280	4920	5640	6370	7100	7830	8550	9090
5 HT	3420	3920	4510	5090	5680	6250	6830	7260

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.