


# FLOTATION 648

<b>TIRE SIZE</b>	<b>600/55 - 26.5</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 BIAS
<b>MACHINERY</b>	EMPACADORA DE HENO / COSECHADORA / ESPARCIDOR / COSECHADORA / MAQUINARIA AGRÍCOLA
<b>VERSIÓN</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS DRIVE WHEEL</b>	160 A8/157 B
<b>LI/SS FREE ROLLING</b>	172 A6/169 B



## DIMENSIONES US STANDARD

<b>CÓDIGO USA</b>	94030972	<b>RC (IN)</b>	158.1
<b>SW (IN)</b>	24.1	<b>RIM REC</b>	AG 20.00
<b>OD (IN)</b>	53.3	<b>ECE</b>	E11-106R-004556
<b>SLR (IN)</b>	22.9	<b>PR</b>	18

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	39	41	42
<b>5 FR</b>	18640	19050	19440
<b>10 FR</b>	16780	17140	17500
<b>20 FR</b>	14910	15230	15550
<b>25 FR</b>	13320	13600	13890
<b>30 FR</b>	11980	12250	12790
<b>5 DW</b>	13320	13610	13890
<b>10 DW</b>	11980	12250	12500
<b>20 DW</b>	10660	10890	11110
<b>25 DW</b>	9510	9720	9920
<b>30 DW</b>	8560	8750	9090

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.