


EARTHMAX SR 55

| | |
|---------------------|--|
| TIRE SIZE | 29.5 R 29 |
| UM | US STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | BULLDOZER / CHARGEUR- TRANSPORTEUR LHD / CHARGEUR |
| VERSION | CUT RESISTANT COMPOUND |
| TIRE TYPE | TL |
| LI/SS | 218 A2 |



DIMENSIONS US STANDARD

| | | | |
|-----------------|----------|--------------------|----------------------|
| CODE USA | 94040193 | RIM REC | 25.00/3.5 |
| OD (IN) | 79.1 | RIM ALT | 24.00/3.5; 26.00/3.5 |
| SLR (IN) | 35.9 | TRA CODE | L5S |
| RC (IN) | 238.1 | STAR RATING | ★★ |

LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 76 | 80 | 83 | 87 | 91 | 94 |
|-----------|-------|-------|-------|-------|-------|-------|
| 5 | 44100 | 45400 | 46700 | 49400 | 50700 | 52000 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.