


# AGRIMAX SIRIO

<b>TIRE SIZE</b>	<b>540/65 R 38</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	TRACTOR DE MARE PUTERE / TRACTOR
<b>VERSION</b>	HIGH SPEED
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	153 D ; 150 E



## DIMENSIUNI IS STANDARD

<b>SW (MM)</b>	530	<b>RIM REC</b>	W 16 L
<b>OD (MM)</b>	1667	<b>RIM ALT</b>	W 18 L
<b>SLR (MM)</b>	769	<b>ECE</b>	E4-106R-000816
<b>RC (MM)</b>	5050	<b>SRI</b>	800

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4
70	1575	1810	2080	2345	2615	2885	3120	3350
65	1720	1975	2265	2555	2850	3140	3395	3650
50	1805	2075	2380	2685	2995	3300	3570	3835
40	1880	2160	2480	2800	3120	3440	3720	4000
25	2040	2340	2685	3035	3380	3725	4030	4330
10	2575	2960	3395	3835	4275	4710	5095	5475

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.