


AGRIMAX V- FLECTO



TIRE SIZE	VF 650/65 R 34 NRO
UM	US STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	TRATTORE A ELEVATA POTENZA / TRATTORE
VERSIONE	STANDARD
TIRE TYPE	TL
LI/SS	170 D

DIMENSIONI US STANDARD

CODICE USA	94074778	RC (IN)	201.2
SW (IN)	25.6	RIM REC	DW 23 B
OD (IN)	67.3	RIM ALT	DW 21 B
SLR (IN)	29.8	ECE	E11-106R-008812

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23	29
45	6130	7100	8060	9140	9990	10950	12040
FROM 40 TO 25	6750	7800	8860	10050	10980	12300	13230
20	6880	7960	9040	10250	11190	12540	13490
12	7010	8110	9210	10450	11410	12790	13760
5	7420	8580	9740	11060	12070	13520	14550
*UPTO 5 CYC WITH FRONT LOADER	9440	10920	12400	14060	15370	17220	18520
5 HT	6880	7960	9040	10250	11190	12540	13490

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.