


# EARTHMAX SR 41

<b>TIRE SIZE</b>	<b>23.5 R 25</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	BULDOZER / ÎNCĂRCĂTOR / BASCULANTĂ ARTICULATĂ (ADT) / AUTOBASCULANTĂ CU PROFIL REDUS (LPDT)
<b>VERSION</b>	CUT RESISTANT COMPOUND
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	185 B ; 195 A2



## DIMENSIUNI US STANDARD

<b>USA CODE</b>	94053353	<b>RIM REC</b>	19.50/2.5
<b>OD (IN)</b>	63.4	<b>TRA CODE</b>	E4/L4
<b>SLR (IN)</b>	28.5	<b>STAR RATING</b>	★★/★
<b>RC (IN)</b>	188.6		

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	58	62	65	69	73	76
30	16500	17100	18200	18700	19800	20400
5	22700	23400	24700	25400	26800	-

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.