


AGRIMAX SPARGO

TIRE SIZE	VF 480/95 R 50
UM	IS STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	TRACTOR
VERSION	STANDARD
TIRE TYPE	TL
LI/SS	181 D



DIMENSIONS IS STANDARD

SW (MM)	479	RIM REC	DW 16 L
OD (MM)	2182	RIM ALT	DW 15 L
SLR (MM)	991	ECE	E11-106R-0010083
RC (MM)	6606	SRI	1025

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	1.0	1.2	1.4	1.6	1.8	2.0	2.2	2.4	2.6	2.8	3.0	3.2
70	4045	4500	5035	5495	5800	6025	6255	6485	6790	7095	7325	7630
FROM 65 TO 40	4375	4865	5445	5940	6270	6515	6765	7015	7345	7675	7920	8250
30	4460	4960	5550	6060	6400	6645	6900	7155	7490	7825	8080	8415
20	4550	5060	5660	6180	6525	6775	7035	7295	7635	7980	8240	8580
10	4810	5350	5985	6535	6900	7165	7440	7715	8075	8440	8715	9075

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.