


MULTIMAX MP 527

| | |
|---------------------|--|
| TIRE SIZE | 460/70 R 24 IND |
| UM | US STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | COMPACT LOADER / TELEHANDLER / COMPACT LOADER / TELEHANDLER |
| VERSION | STANDARD |
| TL/TT | TL |
| LI/SS | 159 A8/B |



DIMENSIONS US STANDARD

| | | | |
|-----------------|----------|----------------|-------------------|
| USA CODE | 94052097 | RC (IN) | 149.6 |
| SW (IN) | 18.3 | RIM REC | DW 15 L |
| OD (IN) | 49.4 | RIM ALT | DW 14 L ; DW 16 L |
| SLR (IN) | 22.6 | ECE | E11-106R-002983 |

LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 23 | 29 | 35 | 41 | 46 | 51 | 58 | 61 | 64 |
|-----------|------|-------|-------|-------|-------|-------|-------|-------|-------|
| 30 | 4630 | 5500 | 6270 | 7140 | 8010 | 8590 | 9640 | - | - |
| 25 | 4630 | 5500 | 6270 | 7140 | 8010 | 8590 | 9640 | - | - |
| 20 | 4960 | 5900 | 6720 | 7650 | 8580 | 9190 | 10330 | - | - |
| 15 | 5150 | 6120 | 6970 | 7940 | 8900 | 9550 | 10710 | - | - |
| 5 CYC. | 5650 | 6960 | 8180 | 9410 | 10710 | 11650 | 13170 | 13900 | 14470 |
| STATIC | 8660 | 10660 | 12540 | 14430 | 16420 | 17870 | 20190 | 21310 | 22190 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.