


# AS 504

<b>TIRE SIZE</b>	<b>11.5/80 - 15.3</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 BIAS
<b>MACHINERY</b>	TELESKOPLADER / FELD-ANHÄNGER / LANDWIRTSCHAFTLICHE GERÄTE / TELESKOPLADER
<b>VERSION</b>	STUBBLE RESISTANT
<b>TIRE TYPE</b>	TL
<b>LI/SS DRIVE WHEEL</b>	123 A8
<b>LI/SS FREE ROLLING</b>	135 A8



## ABMESSUNGEN IS STANDARD

<b>SW (MM)</b>	290	<b>RIM REC</b>	9.00
<b>OD (MM)</b>	867	<b>ECE</b>	E11-106R-007157
<b>SLR (MM)</b>	380	<b>PR</b>	12
<b>RC (MM)</b>	2540	<b>SRI</b>	410

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	4.10
10 FR	3050
25 FR	2595
30 FR	2440
40 FR	2180
10 DW	2170
25 DW	1845
30 DW	1735
40 DW	1550

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.