


AGRIMAX SPARGO

| | |
|---------------------|--|
| TYRE SIZE | VF 320/90 R 46 |
| UM | IS STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | TRACTOR |
| VERSION | STANDARD |
| TYRE TYPE | TL |
| LI/SS | 165 D |



DIMENSIONS IS STANDARD

| | | | |
|-----------------|------|----------------|----------------------------|
| SW (MM) | 323 | RIM REC | W 11 |
| OD (MM) | 1743 | RIM ALT | W 10; DW 10; W 10 L; DW 11 |
| SLR (MM) | 810 | ECE | E11-106R-0010077 |
| RC (MM) | 5316 | SRI | 825 |

LOAD CAPACITY (KG/TYRE)

| KM/H / BAR | 1.0 | 1.2 | 1.4 | 1.6 | 1.8 | 2.0 | 2.2 | 2.4 | 2.6 | 2.8 | 3.0 | 3.2 | 3.4 | 3.6 | 3.8 | 4.0 | 4.2 | 4.4 |
|---------------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|
| 70 | 2050 | 2290 | 2575 | 2815 | 2955 | 3100 | 3195 | 3290 | 3455 | 3625 | 3765 | 3910 | 4030 | 4150 | 4265 | 4385 | 4575 | 4765 |
| FROM 65 TO 40 | 2215 | 2475 | 2785 | 3040 | 3195 | 3350 | 3455 | 3555 | 3735 | 3915 | 4070 | 4255 | 4355 | 4485 | 4610 | 4740 | 4945 | 5150 |
| 30 | 2260 | 2525 | 2840 | 3105 | 3260 | 3420 | 3525 | 3630 | 3810 | 3995 | 4155 | 4310 | 4445 | 4575 | 4705 | 4835 | 5045 | 5255 |
| 20 | 2305 | 2575 | 2895 | 3165 | 3325 | 3485 | 3595 | 3700 | 3890 | 4075 | 4235 | 4400 | 4530 | 4665 | 4800 | 4935 | 5150 | 5360 |
| 10 | 2440 | 2720 | 3060 | 3345 | 3515 | 3685 | 3800 | 3910 | 4110 | 4310 | 4480 | 4650 | 4790 | 4930 | 5075 | 5215 | 5440 | 5665 |
| UPTO 15 CYC. | 3005 | 3355 | 3770 | 4120 | 4330 | 4540 | 4680 | 4820 | 5065 | 5305 | 5515 | 5725 | 5900 | 6075 | 6250 | 6425 | 6705 | 6980 |
| UPTO 30 CYC. | 2520 | 2810 | 3160 | 3455 | 3630 | 3805 | 3920 | 4040 | 4245 | 4450 | 4625 | 4800 | 4945 | 5090 | 5240 | 5385 | 5620 | 5850 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.