

RIDEMAX FROST

TIRE SIZE	540/80 R 38 IND
UM	IS STANDARD
CONSTRUCTION	
MACHINERY	TRACTOR
VERSION	STEEL BELTED
TL/TT	TL
LI/SS	172 A8 ; 167 D



DIMENSIONS IS STANDARD

SW (MM)	550	RIM REC	DW 18 L
OD (MM)	1835	RIM ALT	DW 16 L
SLR (MM)	842	ECE	E11-106R-0010575
RC (MM)	5591	SRI	875

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.8	1.2	1.6	2.0	2.4	2.6	2.8	3.0	3.2
65	2400	3165	3815	4200	4470	4690	4905	5180	5450
50	2595	3420	4125	4540	4830	5070	5305	5600	5890
40	2775	3655	4410	4855	5170	5420	5670	5985	6300
30	2880	3795	4580	5040	5365	5625	5890	6215	6540
20	3025	3985	4810	5290	5635	5910	6185	6530	6870
10	3455	4555	5495	6045	6440	6755	7065	7460	7850
5	4010	5285	6375	7015	7470	7835	8195	8650	9105

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.