


# AGRIMAX RT 765M

|                     |                                                                                                            |
|---------------------|------------------------------------------------------------------------------------------------------------|
| <b>TIRE SIZE</b>    | <b>710/70 R 38</b>                                                                                         |
| <b>UM</b>           | IS STANDARD                                                                                                |
| <b>CONSTRUCTION</b> |  RADIAL                   |
| <b>MACHINERY</b>    | ОПРЫСКИВАТЕЛЬ / ТРАКТОР-ТЯГАЧ / КОМБАЙН ДЛЯ УБОРКИ ВИНОГРАДА / КОМБАЙН / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ |
| <b>VERSION</b>      | STANDARD                                                                                                   |
| <b>TIRE TYPE</b>    | TL                                                                                                         |
| <b>LI/SS</b>        | 175 D ; 178 A8                                                                                             |



## РАЗМЕРЫ IS STANDARD

|                 |      |                 |                 |
|-----------------|------|-----------------|-----------------|
| <b>SW (MM)</b>  | 716  | <b>RIM REC</b>  | DW 23 B         |
| <b>OD (MM)</b>  | 1959 | <b>ECE</b>      | E11-106R-004072 |
| <b>SLR (MM)</b> | 859  | <b>SRI</b>      | 925             |
| <b>RC (MM)</b>  | 5751 | <b>TRA CODE</b> | R1W             |

## LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 0.6  | 0.8  | 1.0  | 1.2  | 1.4  | 1.6  | 2.0  | 2.4  |
|------------|------|------|------|------|------|------|------|------|
| 65         | 2895 | 3325 | 3815 | 4305 | 4800 | 5290 | 5785 | 6150 |
| 50         | 3040 | 3490 | 4010 | 4525 | 5040 | 5560 | 6075 | 6460 |
| 40         | 3150 | 3620 | 4155 | 4690 | 5230 | 5765 | 6300 | 6700 |
| 30         | 3330 | 3825 | 4390 | 4955 | 5520 | 6085 | 6655 | 7075 |
| 10 LT      | 3880 | 4455 | 5115 | 5775 | 6435 | 7095 | 7755 | 8245 |
| 10 HT      | 3330 | 3825 | 4390 | 4955 | 5520 | 6085 | 6655 | 7075 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.