

# AW 729

<b>TIRE SIZE</b>	<b>15.0/55 - 17</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	⊠ BIAS
<b>MACHINERY</b>	BALER / IMPLEMENT MACHINERY / TRAILER / HARVESTER / IMPLEMENTS
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS DRIVE WHEEL</b>	122 A8
<b>LI/SS FREE ROLLING</b>	134 A8



## DIMENSIONS IS STANDARD

<b>SW (MM)</b>	385	<b>RIM REC</b>	13.00
<b>OD (MM)</b>	850	<b>RIM ALT</b>	13; W 13
<b>SLR (MM)</b>	377	<b>ECE</b>	E11-106R-006434
<b>RC (MM)</b>	2560	<b>PR</b>	10

## LOAD CAPACITY (KG/TIRE)

<b>KM/H / BAR</b>	<b>2.60</b>
10 FR	2970
25 FR	2520
30 FR	2375
40 FR	2120
10 DW	2100
25 DW	1785
30 DW	1680
40 DW	1500

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.