

# XL GRIP (E3)

|                     |                      |
|---------------------|----------------------|
| <b>TIRE SIZE</b>    | <b>18.00 - 25</b>    |
| <b>UM</b>           | US STANDARD          |
| <b>CONSTRUCTION</b> | ⊠ BIAS               |
| <b>MACHINERY</b>    | STARRER MULDENKIPPER |
| <b>VERSION</b>      | STANDARD             |
| <b>TIRE TYPE</b>    | TT                   |



## ABMESSUNGEN US STANDARD

|                 |          |                 |           |
|-----------------|----------|-----------------|-----------|
| <b>USA-CODE</b> | 94025817 | <b>RIM REC</b>  | 13.00/2.5 |
| <b>OD (IN)</b>  | 63.6     | <b>RIM ALT</b>  | 15.00/2.5 |
| <b>SLR (IN)</b> | 29.1     | <b>PR</b>       | 40        |
| <b>RC (IN)</b>  | 188.2    | <b>TRA CODE</b> | E3/L3     |

## LOAD CAPACITY (LBS/TIRE)

| <b>MPH / PSI</b> | <b>102</b> | <b>138</b> |
|------------------|------------|------------|
| 30               | 21500      | -          |
| 5                | -          | 37500      |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.