


RIDEMAX FL 693 M



TIRE SIZE	400/45 R 17.5
UM	IS STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	CISTERNĂ / REMORCĂ / MAȘINI DE IMPLEMENTARE
VERSION	STANDARD
TIRE TYPE	TL
LI/SS	139 D

DIMENSIUNI IS STANDARD

SW (MM)	400	RIM REC	14.00
OD (MM)	800	ECE	E11-106R-006619
SLR (MM)	343	SRI	390
RC (MM)	2357		

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.8	1.2	1.6	2.0	2.4	2.8	3.2	3.6	4.0	5.0	6.0
70	555	710	890	1000	1155	1310	1440	1575	1730	1950	2215
65	610	780	975	1095	1265	1435	1580	1730	1900	2140	2430
50	740	945	1180	1330	1535	1740	1915	2095	2300	2595	2945
40	830	1060	1325	1490	1720	1950	2150	2350	2580	2910	3305
30	920	1175	1470	1655	1910	2170	2390	2610	2865	3230	3670
25	960	1230	1540	1730	2000	2270	2500	2730	3000	3380	3840
10	1095	1400	1750	1970	2275	2585	2845	3110	3415	3850	4375

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.