


AGRIMAX V-FLECTO



TIRE SIZE	VF 600/60 R 38
UM	IS STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	MOTORSTARK TRAKTOR / TRAKTOR
VERSION	STANDARD
TIRE TYPE	TL
LI/SS	168 D

DIMENSIONER IS STANDARD

SW (MM)	587	RIM REC	DW 20 B
OD (MM)	1685	RIM ALT	DW 18 L
SLR (MM)	757	ECE	E11-106R-006414
RC (MM)	5077	SRI	800

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4
70	2345	2705	3110	3465	3875	4230	4740	5095
FROM 65 TO 40	2580	2970	3420	3810	4260	4650	5210	5600
30	2630	3030	3485	3885	4340	4740	5315	5710
20	2680	3085	3555	3960	4425	4835	5415	5820
10	2835	3265	3760	4190	4685	5115	5730	6160
*UPTO 10 CYC WITH FRONT LOADER	3610	4160	4785	5335	5960	6510	7295	7840
10 HT	2630	3030	3485	3885	4340	4740	5315	5710

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.