


# EARTHMAX SR 35

|                     |  |
|---------------------|--|
|                     | <b>750/65 R 25</b>   |
| <b>UM</b>           | US STANDARD  |
| <b>CONSTRUCTION</b> |  RADIAL |
| <b>MACHINERY</b>    | YÜKLEYİCİ / YÜK TAŞIMA DAMPERİ<br>(LHD) / YÜKLEYİCİ                                      |
| <b>VERSION</b>      | CUT RESISTANT COMPOUND   |
| <b>TIRE TYPE</b>    | TL   |
|                     | 190 B  |



## UNDEFINED US STANDARD

|                 |          |                    |                     |
|-----------------|----------|--------------------|---------------------|
| <b>USA CODE</b> | 94051786 | <b>RIM REC</b>     | 24.00/3.0           |
| <b>OD (IN)</b>  | 63.0     | <b>RIM ALT</b>     | 22.00/3.0;25.00/3.0 |
| <b>SLR (IN)</b> | 28.1     | <b>TRA CODE</b>    | E3                  |
| <b>RC (IN)</b>  | 189.1    | <b>STAR RATING</b> | ★★                  |

## LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 58    | 62    | 65    | 69    |
|-----------|-------|-------|-------|-------|
| 30        | 20900 | 21500 | 22700 | 23400 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.