

# LOADER SPECIAL



# LOADER SPECIAL



LOADER SPECIAL (L-5) is a bias-ply tire that keeps your loaders on the move and provides top efficiency in heavy-duty rock operations. Optimum traction and exceptional cut resistance will boost productivity.



|      | SIZE      | TT/TL | TRA CODE | PR | LI/SS | RIM                                                                               |         | TMPH | O.W.<br>(in)                                                                        | OD<br>(in)                                                                          | SLR<br>(in)                                                                         | RC<br>(in)                                                                          | THREAD DEPTH | VERSION |
|------|-----------|-------|----------|----|-------|-----------------------------------------------------------------------------------|---------|------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|--------------|---------|
|      |           |       |          |    |       | REC RIM                                                                           | ALT RIM |      |                                                                                     |                                                                                     |                                                                                     |                                                                                     |              |         |
|      |           |       |          |    |       |  |         |      |  |  |  |  |              |         |
| Ø25" | 29.5 - 25 | TL    | L5       | 32 | -     | 25.00/3.5                                                                         | -       | 0    | 30.3                                                                                | 76.0                                                                                | 34.8                                                                                | 226.5                                                                               | 125.37       | STD     |
|      | 26.5 - 25 | TL    | L5       | 28 | -     | 22.00/3.0                                                                         | -       | 0    | 27.0                                                                                | 71.5                                                                                | 32.8                                                                                | 211.5                                                                               | 117.81       | STD     |
|      | 20.5 - 25 | TL    | L5       | 20 | -     | 17.00/2.0                                                                         | -       | 0    | 20.9                                                                                | 61.8                                                                                | 0                                                                                   | 0                                                                                   | 107.1        | STD     |
|      | 29.5 - 25 | TL    | L5       | 28 | -     | 25.00/3.5                                                                         | -       | 0    | 30.3                                                                                | 76.0                                                                                | 34.8                                                                                | 226.5                                                                               | 125.37       | STD     |
|      | 26.5 - 25 | TL    | L5       | 32 | -     | 22.00/3.0                                                                         | -       | 0    | 27.0                                                                                | 71.5                                                                                | 32.8                                                                                | 211.5                                                                               | 117.81       | STD     |

STD: STANDARD, SB: STEEL BELTED

| TECHNOLOGIES                                                                        |                                                                                     |                                                                                     | PERFORMANCES                                                                        |                                                                                     |                                                                                     |
|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|
|  |  |  |  |  |  |
|  |  |                                                                                     |                                                                                     |                                                                                     |                                                                                     |
| -                                                                                   | -                                                                                   |                                                                                     |                                                                                     |                                                                                     |                                                                                     |

Permissible tolerances: O.O. 2%–S.W. 2%–RC 2.5%–LI/SS load/speed index, S.W. tire width O.O. outer diameter of the tire: SLR static radius, RC rolling circumference ; SRI index

|      | SIZE       | TT/TL | TRA CODE | PR | LI/SS | RIM                                                                               |                                                                                   | TMPH | O.W.<br>(in) | OD<br>(in) | SLR<br>(in) | RC<br>(in) | THREAD DEPTH | VERSION |
|------|------------|-------|----------|----|-------|-----------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|------|--------------|------------|-------------|------------|--------------|---------|
|      |            |       |          |    |       | REC RIM                                                                           | ALT RIM                                                                           |      |              |            |             |            |              |         |
|      |            |       |          |    |       |  |  |      |              |            |             |            |              |         |
| Ø33" | 35/65 - 33 | TL    | L5       | 42 | -     | 28.00/3.5                                                                         | -                                                                                 | 0    | 35.8         | 82.9       | 38.4        | 256.1      | 125.37       | STD     |
| Ø39" | 40/65 - 39 | TL    | L5       | 56 | -     | 32.00/4.0                                                                         | -                                                                                 | 0    | 39.4         | 94.7       | 0           | 0          | 136.08       | SB      |
| Ø45" | 45/65 - 45 | TL    | L5       | 58 | -     | 36.00/4.5                                                                         | -                                                                                 | 0    | 46.7         | 109.6      | 0           | 0          | 146.16       | SB      |

STD: STANDARD, SB: STEEL BELTED

| TECHNOLOGIES                                                                                                                                                                            |                                                                                     | PERFORMANCES                                                                                                                                                                                                                                                      |                                                                                                                                                                                         |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <br><br><b>L5</b> |  | <br><br> | <p>Permissible tolerances: 0.0. 2%–S.W. 2%–RC 2.5%–LI/SS load/speed index, S.W. tire width 0.0. outer diameter of the tire: SLR static radius, RC rolling circumference ; SRI index</p> |